BORE TO BE CONCENTRIC WITH PILOT DIA. ON REAR WITHIN .002 INDICATOR READING.

15.125 +.005 -.000 DIA TO GAGE

SURFACES TO BE TRUE & PARALLEL WITH EACH OTHER WITHIN .002

SECTION-E-E

CONTOUR AT "Y"

IMAGINARY CONTOUR OF ARM AT "Z"

VIEW "X" - FROM "Y" TO "Z"

SECTION-G

SECTION-H

SECTION-F

SECTION-I

9/16 DRILL 8 HOLES

RIB

SECTION-A

3.501 ±.001 DIA.

#"I" (.272) TAP DRILL
5/16-24 U.S.S. TAP
P.D. .2854
.2878
4 HOLES

1/32 X 45° CHAMFER

SECTION-D

SECTION-J

ALL DIMENSIONS GIVEN IN THIS SECTION, APPLY TO ALL FOUR FEET

CONTOUR OF ARM MAKES A CONSTANT CHANGE FROM "Y" TO "Z" AS SHOWN IN VIEW "X"

7.4394

5 3/8

13/32 DRILL THRU
3/4 DIA. SPOT FACE ON BACK SIDE
6 HOLES

SECTION-B

4.017

8.082 ±.002 TO CENTER OF STARTING MOTOR FOR 119 T GEAR & 10 T PINION

15 7/8 BOLT CENTERS

10 3/8 BOLT CENTERS

THESE SURFACES ON ALL FOUR FEET TO BE CAST IN A CHILL AND MUST BE SMOOTH; FLAT AND UNIFORM WITH EACH OTHER TO ± 1/32 NO DRAFT BEING USED

SECTION-C

7 19/32 BORE

4 1/16 FIN. BORE THIS DISTANCE

#Q (.332) TAP DRILL - 1 DEEP
3/8-24 U.S.S. TAP - 7/8 DEEP
P.D. .3479
.3503
-3 HOLES
90° CO-SINK - 3/8 DIA.

#Q (.332) TAP DRILL { HOLES R&S - THRU / REMAINING HOLES - 1 DEEP
3/8-24 U.S.S. TAP { HOLES R&S - THRU / REMAINING HOLES - 7/8 DEEP
P.D. .3479
.3503
-12 HOLES
90° CO-SINK - 3/8 DIA.

#Q (.332) TAP DRILL THRU
3/8-24 U.S.S. TAP THRU
P.D. .3479
.3503
-6 HOLES
90° CO-SINK - 3/8 DIA.

SAND BLAST ROUGH CASTING ALL OVER
POLISH & BUFF OUTSIDE - SCRATCH BRUSH SURFACE WHERE POLISHING IS IMPOSSIBLE.

ALL FILLET RADII NOT INDICATED ARE 1/4

NOTE :- THIS RIB IS BUILT HIGHER THAN THE OTHER RIBS

DO NOT SCALE PRINT. WORK TO DIMENSIONS GIVEN. TOLERANCE ±.010 ON ALL FRACTIONAL DIMENSIONS.

MATERIAL #195 ALUMINUM CASTING HEAT TREATED	NAME FLYWHEEL HOUSING
NO REQ'D. 1	DR. L.C. CH'D. JW APPR'D. (MFD)
SCALE FULL	PART NO. J-321
DATE 5-9-28	